ADHESIVE

SDS Revision Date:

JAN2023

1. Product and Company Identification

Product name: Product type Restriction of Use:

Company address:

Adhesive R & D Inc. 4603 Anderson Drive Eau Claire, WI. 54703 Hydraulic Beast Anaerobic thread locker None

Contact information: Telephone: 1 (715) 832-4557

2. Hazard(s) identification

WARNING:

EMERGENCY OVERVIEW CAUSES SKIN AND EYE IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
Acute Toxicity - Oral	4
Acute Toxicity - Dermal	4
Acute Toxicity - Inhalation	4
Skin corrosion/irritation	2
Serious eye damage	2A
Carcinogenicity	2
Specific target organ toxicity	2

PICTOGRAM(S)



Precautionary Statements

Prevention:

Response:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat / sparks / open flames / hot surfaces - No smoking. Avoid breathing dust / fume / gas / mist / vapors / spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection.

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air. Call a POISON CENTER or doctor / physician if you feel unwell. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth. P308+313 IF exposed or concerned: Get medical advice / attention. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice /



Storage:

Disposal:

Safety Data Sheet Hydraulic Beast

SDS Revision Date:

JAN2023

attention. If eye irritation persists: Get medical advice / attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Take off contaminated clothing and wash before reuse.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial, and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section11 for additional toxicological information.

3. Composition/information on ingredients

Hazardous Component(s)	CAS Number	Percentage*	
Proprietary Elastomeric Pre-Polymer	Proprietary	60 - 90	
Hydroxyethyl methacrylate	868-77-9	40 - 10	
Saccharin	81-07-2	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 3	
Amorphous Silica	67762-90-7	5 - 15	
Cumene	98-82-8	0.1 - 1	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 3	

*Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. First aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention Never give anything by mouth to an unconscious person.
Inhalation:	Remove to fresh air, keep victim at rest in a comfortable breathing position. Get medical attention if irritation persists.
Skin contact:	Wash skin with soap and water. If irritation persists, call physician.
Eye contact:	Immediately flush with plenty of water for several minutes. Get medical attention if irritation persists.
Ingestion:	If swallowed DO NOT induce vomiting. Get medical attention if irritation persists.
Symptoms:	See Section 11.

5. Fire fighting measures

Extinguishing media:	Carbon Dioxide, Dry Chemicals, Foam	
Special firefighting procedures:	A self-contained breathing apparatus is required.	
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or runture of storage containers	
	explosions or rupture of storage containers.	



SDS Revision Date:

JAN2023

Hazardous combustion products:

Avoid breathing dust / fume / gas / mist / vapors / spray.

6. Accidental release measures

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Unusual fire or explosion hazards:	Do not allow spills to enter drains or waterways. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
Hazardous combustion products:	DO NOT use cloth materials. In case of a leak or spill, flood area with water to polymerize the material. Soak up with inert absorbent. Ventilate area. Prevent product from entering drains.

7. Handling and storage

Handling:	Avoid contact with skin and eyes. Avoid breathing vapors. Handle containers carefully to prevent damage and spillage. Refer to Section 8.
Hazardous combustion products:	Store in a cool dry area, away from heat, sparks, and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

8. Exposure controls and personal protection

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Proprietary Elastomeric Pre- Polymer	None	None	None	None
Hydroxyethyl methacrylate	None	None	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	None	None
Amorphous Silica	None	None	None	None
Cumene	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eye/face protection:	Protective safety glasses recommended.

SDS Revision Date:

JAN2023

Skin protection:

Other Work Practices

Use polyethylene gloves and aprons. DO NOT use cotton/cloth gloves.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

9. Physical and chemical properties

Color:BrownOdor:MildOdor threshold:Not available.pH:Not applicableVapor pressure:Not available.Boiling point/range:> 149 °C (> 300.2 °F)Melting point/ range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not available.Flammability:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.Decomposition temperature:Not available.	Physical state:	Liquid
Odor threshold:Not available.pH:Not applicableVapor pressure:Not available.Boiling point/range:> 149 °C (> 300.2 °F)Melting point/ range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not determinedFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedFlammability:Not available.Flammability:Not available.Flammability:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Color:	Brown
pH:Not applicableVapor pressure:Not available.Boiling point/range:> 149 °C (> 300.2 °F)Melting point/range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedFlammable/Ising to the projection rate:Not applicableFlammable/Ising to the projection rate:Not applicableFlammable/Ising to the projection rate:Not available.Solubility in water:Not applicableFlammability:Not available.Vot content:Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Odor:	Mild
Vapor pressure:Not available.Boiling point/range:> 149 °C (> 300.2 °F)Melting point/ range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not applicableFlammability:Not applicableFlammability:Not applicableParition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Odor threshold:	Not available.
Boiling point/range:> 149 °C (> 300.2 °F)Melting point/range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableFundation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	pH:	Not applicable
Melting point/ range:Not available.Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Vapor pressure:	Not available.
Specific gravity:1.1 at 23.9 °C (75.02 °F)Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableFummability:Not applicablePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Boiling point/range:	> 149 °C (> 300.2 °F)
Vapor density:Not available.Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Melting point/ range:	Not available.
Flash point:> 93.3 °C (> 199.94 °F) Tagliabue closed cupFlame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Specific gravity:	1.1 at 23.9 °C (75.02 °F)
Flame projection:Not applicableFlammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Vapor density:	Not available.
Flammable/Explosive limits - lower:Not determinedFlammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Flash point:	> 93.3 °C (> 199.94 °F) Tagliabue closed cup
Flammable/Explosive limits - upper:Not determinedAutoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Flame projection:	Not applicable
Autoignition temperature:Not determinedFlammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Flammable/Explosive limits - lower:	Not determined
Flammability:Not applicableEvaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Flammable/Explosive limits - upper:	Not determined
Evaporation rate:Not available.Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Autoignition temperature:	Not determined
Solubility in water:InsolublePartition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Flammability:	Not applicable
Partition coefficient (n-octanol/water):Not available.VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Evaporation rate:	Not available.
VOC content:0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)Viscosity:Not available.	Solubility in water:	Insoluble
Viscosity: Not available.	Partition coefficient (n-octanol/water):	Not available.
	VOC content:	0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)
Decomposition temperature: Not available.	Viscosity:	Not available.
	Decomposition temperature:	Not available.



SDS Revision Date:

JAN2023

10. Stability and reactivity		
Stability:	Stable under normal circumstances.	
Hazardous Reactions:	No data available.	
Hazardous decomposition products:	Carbon oxides	
Incompatible materials:	Strong oxidizing agents, Peroxides, Reducing agents.	
Reactivity:	Hazardous Polymerization will not occur.	
Conditions to avoid:	Excessive Heat.	

11. Toxicological information

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Proprietary Elastomeric Pre-Polymer	None	None
Hydroxyethyl methacrylate	None	None
Saccharin	None	None
Cumene hydroperoxide	Oral LD50 (Rat) = 382 mg/kg Skin LD50 (Rabbit) =0.126 mL/kg Inhalation LC50 (Rat, 4 h) =220ppm	None
Amorphous Silica	None	None
Cumene	None	None
1-Acetyl-2-phenylhydrazine	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Proprietary Elastomeric Pre-Polymer	No	No	No
Hydroxyethyl methacrylate	No	No	No
Saccharin	No	No	No
Cumene hydroperoxide	No	Group 3	No
Amorphous Silica	No	No	No
Cumene	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No



SDS Revision Date:

JAN2023

12. Ecological information

Ecological information:

Toxic to aquatic life

Aquatic Ecotoxicity

Aquatic Ecoloxicity				
Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Cumene Hydroperoxide CAS# 80-15-9	3.9:96 h Oncorhynchus mykiss	7:24 h Daphnia magna	Not Available	
Saccharin	18300:96 Pimephales promelas	Not Available	Not Available	

13. Disposal considerations

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Observe all federal, state and local regulations when disposing of this substance.

Cumene Hydroperoxide CAS # 80-15-9 RCRA-U Series Wastes [U096]

14. Transport information

The transport information provided in this section only applies to the material/formulation itself and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

	,
Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
DOT Hazardous Substance(s):	Not regulated
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packing group:	Not regulated
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packing group:	Not regulated

15. Regulatory information

United States Regulatory Information



SDS Revision Date:

JAN2023

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	Complies Complies
CERCLA/SARA Section 302 EHS:	This product contains one or more substances regulated under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302). Cumene Hydroperoxide (CAS# 80-15-9) 10lbs. (4.54kg)
CERCLA/SARA Section 311/312:	Acute health hazard
CERCLA/SARA Section 313:	Section 313 of title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372. Cumene Hydroperoxide (CAS# 80-15-9). Saccharin (CAS# 81-07-2).
CERCLA Reportable quantity:	Cumene Hydroperoxide (CAS# 80-15-9) 10lbs. (4.54kg)
California Proposition 65:	Titanium Dioxide (13463-67-7). Carcinogen.
da Poquiatory Information	

Canada Regulatory Information

CEPA DSL/NDSL Status:

None

01/2023

16. Other information

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Adhesive R&D Technical Staff

Issue date:

IMPORTANT: The information presented herein, while not guaranteed, was prepared in good faith, and is known to be true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE, OR OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or violate any federal, state, or local laws, rules, regulations or ordinances.