

ADHESIVE



EP100 MSDS

HEALTH HAZARDS:

DATE ISSUED: Ver2013

HEALTH: 2
FIRE: 1
REACTIVITY: 0
FLASH POINT: >300°F

METHOD USED: PMCC

PRODUCT NAME

COMMON CODE:

EP100

HAZARD MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS:

Plastic Materials - Paste

NOIBN

Not Hazardous by D.O.T.

CHEMICAL FAMILY

FORMULA

Epoxy Resin - Formulated

Proprietary

HAZARDOUS INGREDIENTS

CAS #	% (optional)	CHEMICAL NAMES	TLV/PEL
25068-38-6	---	Epoxy Resin	---

CAS #	% (optional)	CHEMICAL NAMES	TLV/PEL
90-72-2	< 100%	CATALYST	---

KEY: --- LIMITS HAVE NOT BEEN ESTABLISHED

PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point: >500°F
Vapor Pressure: 0.03 mm Hg @ 77°C
Vapor Density (air=1): NA
Solubility in water: Negligible
Specific gravity (H₂O=1): 0.996
Percent volatile by volume (%): 0%
Evaporation rate: (=1): NA
Percent solid by weight (%): 100%
Appearance and odor: Blue translucent clinging paste with slight aromatic odor.
Analytical: 8.30 lbs/gal

FIRE AND EXPLOSION DATA

Flammable Limits: LEL Not Established UEL Not established
Extinguishing Media: Water, fog, foam, dry chemical, CO₂
Special Fire Fighting Procedures: Do not enter confined fire space without full protective gear including a positive pressure, self-contained, NIOSH approved breathing apparatus. Cool fire exposed container with water.
Unusual Fire and Explosion Hazard: Container areas exposed to intense heat or flame should be cooled with H₂O to prevent pressure build-up and/or weakening of container structure.

REACTIVITY DATA

Stability: Stable

ADHESIVE



Conditions to Avoid:	Avoid high temperatures, open flames and unscheduled contact with curing agents.
Incompatibility: (Materials to Avoid)	Incompatible with strong oxidizing agents, strong acids and bases, secondary aliphatic amines and mercaptans.
Hazardous Decomposition Products:	Carbon dioxide (CO ₂) Carbon Monoxide (CO), aldehydes, acids and other organic substances may be formed during high temperature degradation.
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Avoid mixing resin and hardener in uncontrollable quantities.

HEALTH HAZARD DATA

Chemical Listed as Carcinogen or Potential Carcinogen in NTP, IARC or OSHA 1910(Z)	This material is neither carcinogenic nor potentially carcinogenic.
---	---

EFFECTS OF OVEREXPOSURE

Skin Contact:	Product could be moderately irritating to skin. May cause allergic skin reaction in susceptible individuals. Avoid direct skin contact when using this material.
Eye Contact:	Product could be moderately irritating to the eyes. Avoid touching eyes when using this material.
Inhalation:	Because of its low volatility this product is not likely to be an inhalation hazard.
Ingestion:	No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

Primary Routes of Entry:

Inhalation:	Skin Contact	Other (Specify)
--------------------	---------------------	------------------------

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation:	Remove victim to fresh air.
Eyes:	Flush eyes with generous amounts of water for a least 15 minutes. GET MEDICAL ATTENTION if it appears necessary.
Skin:	Wash thoroughly with soap and water.
Ingestion:	In general, no treatment is necessary unless large quantities of product are ingested.

OCCUPATIONAL EXPOSURE LIMITS

OSHA Permissible Exposure Limit:	OSHA limits have not been established for this product.
ACGIH Threshold Limit Value:	ACGIH limits have not been established for this product.

SPECIAL PROTECTION INFORMATION

Respiratory Protection:	No respiratory protection should be needed.
Ventilation:	Local exhaust is recommended. Mechanical exhaust can be used as a back up system.
Protective Gloves:	Chemical resistant gloves such as PVA.
Eye Protection:	NIOSH approved safety glasses or goggles with side shields.
Other Protective Clothing or Equipment:	Chemical resistant clothing as required to minimize skin contact.

ADHESIVE



SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Use cautious judgment when cleaning spills. Small spills may be collected with absorbent material , such as clay or sand. Large spills should be diked and contained with absorbent materials. Flush area with water spray to remove residue. Dispose of flush legally.
Waste Disposal Methods:	Dispose in accordance with local, state and federal regulations.

SPECIAL PRECAUTIONS

Precaution to be Taken in Handling and Storage:	Store at ambient temperatures in well ventilated area. Avoid sparks, open flames and extreme heat. Store separately from amine curing agents. Protect container from physical damage.
Other Precautions:	Container, even those that have been emptied, can contain product residues. Handle in accordance with good industrial practices. Avoid prolonged or repeated contact with skin. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Launder contaminate clothing before use.

KEY ---- Limits have not been established

NA - Not Applicable

UI - Unavailable Information

The information supplied here is based on data we consider to be accurate. No warranty, expressed or implied is made. This information is offered solely for you consideration, interpretation and information.