



# MOLY SHIELD™

MOLY SHIELD

Molybdenum Disulfide is a low friction lubricant which provides protection under extreme loads, and will withstand pressures up to .5 million PSI. The suspension of molybdenum disulfide in a premium-grade grease provides excellent lubricity and extreme pressure resistance. Use **MOLY SHIELD™** wherever high loads are encountered, and temperatures do not exceed 650°F.

## PHYSICAL PROPERTIES

Color	Dark Grey
Temperature Range	-65° to 650°F
NLGI Grade	1
Specific Gravity	1.5
Penetration	220±20
Drop Point	380°F
Flash Point: C.O.C.	450°F
Particle Size	1 Mil Maximum

*We believe the information contained herein is current and accurate as of this date of this Technical Data Sheet. Since the use of this information and these opinions and the conditions of use of this product are not under the control of ANTI-SEIZE R&D, Inc. or its agents or distributors, it is the user's obligation to determine the conditions of safe use of this product. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. ANTI-SEIZE R&D, Inc. warrants that the product conforms with ANTI-SEIZE R&D, Inc.'s written specifications, and is free from defects and disclaims all other warranties, expressed or implied and is not responsible for loss claim of damages resulting from the use of its products.*

Rev 01/03