ADHESIVE < ReD

SDS Revision Date:

AUG 2024

1. Product and Company Identification

Product name: Product type Restriction of Use: Company address: Adhesive R & D Inc. 4603 Anderson Drive Eau Claire, WI. 54703 **Deadbolt 70** Anaerobic thread locker None

nread locker

IDH number: Item number: Region: Contact information: Telephone: 1 (715) 832-4557

2. Hazard(s) identification

WARNING:

EMERGENCY OVERVIEW CAUSES SKIN AND EYE IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
Acute Toxicity - Oral	3
Acute Toxicity - Dermal	4
Acute Toxicity - Inhalation	4
Skin corrosive	1B
Specific Target Organ Toxicity (STOT) Repeated Exposure	2
Carcinogen	1B
Specific Target Organ Toxicity Short Term Exposure	3
Skin Irritant	2
Eye Irritant	2
Skin Sensitizer	1

PICTOGRAM(S)

Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat / sparks / open flames / hot surfaces - No smoking. Avoid breathing dust / fume / gas / mist / vapors / spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection.



SDS Revision Date:

AUG 2024

Response:	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim
	to fresh air. Call a POISON CENTER or doctor / physician if you feel unwell. IF
	IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If swallowed: Call a poison
	center or doctor/physician if you feel unwell. Rinse mouth. P308+313 IF
	exposed or concerned: Get medical advice / attention. Specific treatment (see
	information on this label). If skin irritation occurs: Get medical advice / attention.
	If eye irritation persists: Get medical advice / attention. Remove victim to fresh
	air and keep at rest in a position comfortable for breathing. Take off
	contaminated clothing and wash before reuse.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial, and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section11 for additional toxicological information.

3. Composition/information on ingredients

Hazardous Component(s)	CAS Number	Percentage*
2,2-bis 4-(2',3" epoxy propoxy) phenyl propane with hydroxyethylmethacrylate maleic acid half ester.	Proprietary	60 - 90
Hydroxyethyl methacrylate	868-77-9	10 - 40
Saccharin	81-07-2	1 - 5
Cumene hydroperoxide	80-15-9	1 - 3
Cumene	98-82-8	0.1 - 1
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 3

*Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. First aid measures			
General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.		
Inhalation:	Remove to fresh air, keep victim at rest in a comfortable breathing position. Get medical attention if irritation persists.		
Skin contact:	Wash skin with soap and water. If irritation persists, call physician.		
Eye contact:	Immediately flush with plenty of water for several minutes. Get medical attention if irritation persists.		
Ingestion:	If swallowed DO NOT induce vomiting. Get medical attention if irritation persists.		
Symptoms:	See Section 11.		



SDS Revision Date:

AUG 2024

5. Fire fighting measures

Extinguishing media: Special firefighting procedures:

Unusual fire or explosion hazards:

Carbon Dioxide, Dry Chemicals, Foam A self-contained breathing apparatus is required.

Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

Hazardous combustion products:

Avoid breathing dust / fume / gas / mist / vapors / spray.

6. Accidental release measures

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Unusual fire or explosion hazards:

Do not allow spills to enter drains or waterways. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Hazardous combustion products:

DO NOT use cloth materials. In case of a leak or spill, flood area with water to polymerize the material. Soak up with inert absorbent. Ventilate area. Prevent product from entering drains.

7. Handling and storage

Handling:

Avoid contact with skin and eyes. Avoid breathing vapors. Handle containers carefully to prevent damage and spillage. Refer to Section 8.

Hazardous combustion products:

Store in a cool dry area, away from heat, sparks, and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

ADHESIVE

SDS Revision Date:

AUG 2024

8. Exposure controls and personal protection

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
2,2-bis 4-(2',3" epoxy propoxy) phenyl propane with hydroxyethylmethacrylate maleic acid half ester.	None	None	None	None
Hydroxyethyl methacrylate	None	None	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (skin)	None
Amorphous Silica	None	None	None	None
Cumene	None	50 ppm TWA	None	NIOSH - 50 ppm (skin) TWA

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eye/face protection:	Protective safety glasses recommended.
Skin protection:	Use polyethylene gloves and aprons. DO NOT use cotton/cloth gloves.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

9. Physical and chemical properties			
Physical state:	hysical state:		
Color:	Green		
Odor:	Mild		
Odor threshold:	Not Measured		
pH:	Not Measured		
Vapor pressure:	Not Measured		
Boiling point/range:	> 149 °C (> 300.2 °F)	> 149 °C (> 300.2 °F)	
Melting point/ range:	Not Measured		
Specific gravity:	1.1 at 23.9 °C (75.02 °F)	1.1 at 23.9 °C (75.02 °F)	
Vapor density:	lensity: Not Measured		
Flash point:	> 93.3 °C (> 199.94 °F) Tagliabue closed cup		

ADHESIVE

SDS Revision Date:

AUG 2024

Flame projection:	Not Measured
Flammable/Explosive limits - lower:	Not Measured
Flammable/Explosive limits - upper:	Not Measured
Autoignition temperature:	Not Measured
Flammability:	Not Measured
Evaporation rate:	Not Measured
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not Measured
VOC content:	0.56 %; 6.17 g/l (California SCAQMD Method 316B) (Estimated)
Viscosity:	Not Measured
Decomposition temperature:	Not Measured

10. Stability and reactivity

Stability:	Stable under normal circumstances.
Hazardous Reactions:	No data available.
Hazardous decomposition products:	Carbon oxides
Incompatible materials:	Strong oxidizing agents, Peroxides, Reducing agents.
Reactivity:	Hazardous Polymerization will not occur.
Conditions to avoid:	Excessive Heat.



SDS Revision Date:

AUG 2024

11. Toxicological information

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:

Skin contact:
Eye contact:
Ingestion:

Inhalation of vapors or mists of the product may be irritating to the respiratory system. Causes skin irritation. May cause allergic skin reaction. Causes eye irritation. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
2,2-bis 4-(2',3" epoxy propoxy) phenyl propane with hydroxyethylmethacrylate maleic acid half ester.	None	None
Hydroxyethyl methacrylate	Oral LD50 (mouse) = 3275 mg/kg Intraperitoneal LD50 (mouse) = 497 mg/kg Intravenous LDLo (dog) 99,200 nL/kg Oral LD50 (guinea pig) = 4680 mg/kg Oral LD50 (rat) = 5050 mg/kg	None
Saccharin	oral LD50 mouse = 17 gm/kg	None
Cumene hydroperoxide	Oral LD50 (rat) = 382 mg/kg Inhalation LD50 (rat) = 220ppm/4H Skin LD50 (rat) = 500 mg/kg Subcutaneous LD50 (rat) = 382 kg/kg oral LDLo (mouse) = 5 gm/kg	None
Cumene	Inhalation TCLo (human) = 200ppm Oral LD50 (rat) = 1400 mg/lg Inhalation LCLo (rat) = 8000ppm/4H Oral LD50 (mouse) = 12,750 mg/kg Inhalation LC50 (mouse) = 10 gm/m3/7H	None
1-Acetyl-2-phenylhydrazine	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
2,2-bis 4-(2',3'' epoxy propoxy) phenyl propane with hydroxyethylmethacrylate maleic acid half ester.	No	No	No
Hydroxyethyl methacrylate	No	No	No
Saccharin	No	Group 3	No
Cumene hydroperoxide	No	No	No
Cumene	No	Group 2B	No
1-Acetyl-2-phenylhydrazine	No	No	No



SDS Revision Date:

AUG 2024

12. Ecological information

Ecological information: Aquatic Ecotoxicity

Toxic to aquatic life

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Cumene Hydroperoxide CAS# 80-15-9	3.9:96 h Oncorhynchus mykiss	7:24 h Daphnia magna	Not Available
Saccharin	18300:96 Pimephales promelas	Not Available	Not Available

13. Disposal considerations

Information provided is for unused product only.

Recommended method of disposal:

Observe all federal, state and local regulations when disposing of this substance. None.

Hazardous waste number:

14. Transport information

The transport information provided in this section only applies to the material/formulation itself and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
DOT Hazardous Substance(s):	Not regulated
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packing group:	Not regulated
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	Not regulated
Identification number:	Not regulated
Packing group:	Not regulated



SDS Revision Date:

AUG 2024

15. Regulatory information

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	Complies Complies
CERCLA/SARA Section 302 EHS CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	Acute health hazard Section 313 of title III of the Superfund Amendments and Reauthorization
CERCLA Reportable quantity:	Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372. Cumene Hydroperoxide (CAS# 80-15-9). Cumene Hydroperoxide (CAS# 80-15-9) 10lbs. (4.54kg)
California Proposition 65: Canada Regulatory Information	Cumene (CAS# 98-82-8) 5,000lbs. Cumene - Cancer (04/06/2010) - Authoritative Bodies-National Toxicology Program
CEPA DSL/NDSL Status:	Cumene (CAS# 98-82-8) 10 tons (20,000lbs) Cumene Hydroperoxide (CAS# 80-15-9) 10 tons (20,000lbs)
REACH Regulations	Cumene (CAS# 98-82-8) REACH Annex XVII CMRs Carcinogens: Category 1B

16. Other information

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by:	Cory White - Small Business EHS
--------------	---------------------------------

Issue date:

08/22/24

IMPORTANT: The information presented herein, while not guaranteed, was prepared in good faith, and is known to be true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE, OR OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or violate any federal, state, or local laws, rules, regulations or ordinances.